

## iR1020 Series (A4)

iR1020, iR1024A, iR1024F,  
iR1024i, iR1024iF

## imageRUNNER 2500 Series (A3)

imageRUNNER 2520/i, 2525/i,  
2530/i, 2535/i, 2545/i

**you can**

Compact black-and-white  
multifunctional printers  
for small-to-medium-  
sized workgroups.



imageRUNNER

**Canon**

# Specifications: iR1020/iR1024 Series

Type	Desktop
Maximum Original Size	A4
Copy Sizes	Cassette: A4, Stack Bypass: A5 - A4, Envelopes
Resolution	Copying: 600dpi x 600dpi
Copy/Print Speed	Printing: 1200dpi equivalent x 600dpi (PCL, UFR II LT) 256 Gradations A4: 20cpm (iR1020), 24cpm (iR1024A/24F/24i/24iF) From Stack Bypass 23ppm (iR1024A/24F/24i/24iF)
Magnification	Zoom: 50-200%, Fixed: 50%, 70%, 100%, 141%, 200%
First Copy Time	8.0 sec or less (iR1020), 12.0 sec or less (iR1024A/24F/24i/24iF)
Warm-Up Time	less than 16 sec for iR1020/24A/24F, less than 19 sec for iR1024i/24iF
Multiple Copies/Prints	1 to 99 sheets
Duplexing	(Standard for all models) Automatic stackless
Paper Weight	Cassette: 64 to 90g/m <sup>2</sup> , Stack Bypass: 56 to 128g/m <sup>2</sup> , Duplex: 64 to 80g/m <sup>2</sup>
Cassette	A4
Paper Capacity	500 sheets x 1 cassette, Stack Bypass: 100 sheets
Standard	500 sheets x 1 cassette, Max. total paper capacity: 1,100 sheets
Optional	Canon Custom Processor, 192MHz
CPU	128MB (iR1020/24A/24F), 256MB (iR1024i/24iF)
Memory	
Interface	iR1020/24A/24F Ethernet (100Base-TX/10Base-T) optional, USB2.0 iR1024i/iF Ethernet (100Base-TX/10Base-T), USB2.0
Power Supply	220V AC to 240V AC ±10% (50/60Hz)
Power Consumption	(W) 1023W max.
Dimensions (W x D x H)	520 x 457 x 378mm (iR1020) 520 x 457 x 453mm (iR1024A/24F/24i/24iF) Approx. 22.0kg (iR1020) Approx. 24.1kg (iR1024A/24F/24i/24iF)
Weight	
SEND FUNCTION <sup>1</sup>	
Scan Speed with DADF	BW: 20ipm A4 300dpi, Colour: 6ipm A4 300dpi

Scan Resolution	BW: Up to 600 x 600dpi, Colour: Up to 300 x 300dpi 300dpi (High compression PDF)
Destinations	E-Mail/Internet FAX (SMTP), PC (SMB, FTP), iWDM Gateway
Address Book	Local (Max. 200)
File Format	TIFF, JPEG, PDF, High compression PDF
<b>PRINTER FUNCTION</b>	
PDL	UFR II LT (Standard for iR1020/24A/24F/24i/24iF), PCL 5e/6 (Standard for iR1024i/24iF)
Resolution	1200dpi equivalent x 600dpi (PCL, UFR II LT)
Memory	128MB (iR1020/24A/24F), 256MB (iR1024i/24iF)
CPU	Canon Custom Processor, 192MHz (Uses Main Unit CPU)
PCL Fonts	Roman 113 (including Barcode Fonts)
Supported OS	PCL: Windows 2000/XP/Server 2003/Server 2008/Vista UFR II: Windows 2000/XP/Server 2003/Server 2008/Vista/ Mac OS X 10.2.8 or later
Interface	iR1020/24A/24F Ethernet (100Base-TX/10Base-T) optional, USB2.0 iR1024i/iF Ethernet (100Base-TX/10Base-T), USB2.0
Network Protocol	TCP/IP (LPD/RAW/Port 9100)
<b>DADF<sup>2</sup></b>	
Paper Size	A4R, A5R, A5
Paper Weight	50g/m <sup>2</sup> to 105g/m <sup>2</sup>
Scanning Speed (max.)	A5R to A4: 50 sheets (80g/m <sup>2</sup> ) Copy iR1024A/1024F/1024i/1024iF: A4 20ipm Scan BW: 20ipm A4 300dpi, Colour: 6ipm A4 300dpi
<b>OTHER ACCESSORIES</b>	iR1020/24 Plain Pedestal, Cassette Feeding Module N2, Cassette AD1, Card Reader-E1, Card Reader Attachment D2, NW IF ADAPTOR IN-E11 (Standard for iR1024i/24iF), PCL PRINT KIT-AB1 (Standard for iR1024i/24iF)
	<sup>1</sup> Standard for iR1024i/24iF only <sup>2</sup> Standard for iR1024A/24F/24i/24iF

# Specifications: imageRUNNER 2500 Series

Type	Desktop or Free-standing, (Reader-Printer Combined)
Maximum Original Size	A3
Copy Sizes	Cassette: A5R - A3 Stack Bypass: A5R - A3, Envelopes
Copy/Print Speed (BW)	A4: 2545i/2545: 45ppm, 2535i/2535: 35ppm, 2530i/2530: 30ppm, 2525i/2525: 25ppm, 2520i/2520: 20ppm A3: 2545i/2545/2535i/2535: 22ppm, 2530i/2530/2525i/2525/ 2520i/2520: 15ppm
Magnification	Zoom: 25-400%, Fixed: 25%, 50%, 70%, 100%, 141%, 200%, 400%
First Copy Time	3.9 sec: 2545/35, 5.4 sec: 2530/25, 6.4 sec: 2520
Warm-Up Time	30 seconds
Multiple Copies/Prints	1 to 999 sheets
Duplexing	Standard
Paper Capacity	Standard: 2 x 550-sheet cassettes (80g/m <sup>2</sup> ), (1 x 250-sheet cassette for the imageRUNNER 2520i/2520) Cassette 1: 550 sheets (80g/m <sup>2</sup> ), (250 sheets for the 2520i/2520) Cassette 2: 550 sheets for 2525/i, 2530/i, 2535/i, 2545/i only Stack Bypass: 100 sheets (A4, A4R, A5), 50 sheets (A3) Optional: 550 sheets x 2 cassettes, 550 sheets x 1 cassette for imageRUNNER 2520/2520i only Total Capacity: 2,300 sheets, (2,000 sheets for the 2520i/2520) Canon Custom Processor, 400MHz
CPU	512MB (i models), 256MB (non i models)
Memory	
Interface	Ethernet (100Base-TX/10Base-T), USB Host I/F 2.0, USB Device 1.0
Power Supply	220-240V AC, 50/60Hz, 4.2A (45/35ppm model), 220-240V AC, 50/60Hz, 3.3A (35/30/20ppm model)
Power Consumption	1.827kW (45/35ppm model), 1.345kW (30/25ppm), 1.542kW (20ppm model)
Dimensions (W x D x H)	2545i/2545/2535i/2535: 565 x 680 x 806mm, 565 x 689 x 907mm (with the DADF), 2530i/2530/2525i/2525: 565 x 680 x 806mm, 565 x 689 x 896mm (with the DADF), 2520i/2520: 565 x 680 x 681mm, 565 x 689 x 771mm (with the DADF)
Weight	2545i/2535i: Approx. 78.4kg, 2545/2535: Approx. 70.5kg 2530i/2525i: Approx. 77.5kg, 2530/2525: Approx. 68.0kg 2520i: Approx. 56.0kg, 2520: Approx. 50.5kg
<b>PRINT SPECIFICATION</b>	
PDL	UFR II-LT, PCL5e/6 (standard on i models, optional on non i models), PostScript level 3 emulation (optional)
Resolution	600 x 600dpi, 1200 x 1200dpi (UFR II-LT only)
CPU	Canon Custom Processor, 400MHz
Fonts	PS Fonts: Roman 136; PCL Fonts: Roman 93
Supported OS	Windows 2000/XP/Server 2003/Vista/Server 2008/Windows 7, Mac OS X (10.4 or later), Linux
Interface	Ethernet (100Base-TX/10Base-T)
Network Protocol	TCP/IP (LPD/Port9100, HTTP), SMB, SNMPv1, WSD, IPv4/IPv6 support
Pull Scan	Network TWAIN Driver
<b>SEND SPECIFICATION/ CLR SEND KIT-Y1</b>	(standard on i models, optional on non i models)
Scan Speed (A4, 300dpi, BW/Colour)	45/34ipm (45/35ppm model), 25/13ipm (30/25/20ppm model)
Scan Resolution	BW: Up to 600 x 600dpi, Colour: Up to 300 x 300dpi
Destinations	E-Mail/Internet FAX (SMTP), PC/Server (SMB, FTP), iWDM, USB memory key
Address Book	Local (Max.500)
File Format	TIFF, JPEG, PDF, High compression PDF, Searchable PDF (with optional Searchable PDF-C1)

<b>DADF-AA1</b>	<b>for imageRUNNER 2545/2535</b>
Paper Size	A3, A4, A4R, A5, A5R
Paper Weight	Single sided original: 42 to 128g/m <sup>2</sup> , Double-sided original: 50 to 128g/m <sup>2</sup>
Max. Number of Originals	100 sheets (A4, A4R, A5, A5R: 80g/m <sup>2</sup> ), 50 sheets (A3: 80g/m <sup>2</sup> )
Scanning Speed (max.)	Copy: 45ipm (A4, 600 x 600dpi) Scan: 45/34ipm
Dimensions (W x D x H)	565 x 540 x 137mm
Weight	Approx. 7.9kg
<b>DADF-AB1</b>	<b>for imageRUNNER 2530/2525/2520</b>
Paper Size	A3, A4, A4R, A5, A5R
Paper Weight	Single sided original: 37 to 128g/m <sup>2</sup> , Double-sided original: 50 to 128g/m <sup>2</sup>
Max. Number of Originals	50 sheets (A4, A4R, A5, A5R: 80g/m <sup>2</sup> ), 25 sheets (A3: 80g/m <sup>2</sup> )
Scanning Speed (max.)	Copy: 25ipm (A4, 600 x 600dpi: BW) Scan: 25/13ipm
Dimensions (W x D x H)	565 x 544 x 126mm
Weight	Approx. 7.0kg
<b>CASSETTE UNIT-W1</b>	<b>for imageRUNNER 2520/i</b>
Type	Front-loading adjustable drawers
Paper Size	A3, A4, A4R, A5R, Custom size 139.7 to 297mm x 182 to 432mm
Paper Capacity and	
Weight	550 sheets (80g/m <sup>2</sup> ) x 1 cassette, 64 to 90g/m <sup>2</sup>
Dimensions (W x D x H)	565 x 680 x 97mm
Weight	Approx. 12.8kg
<b>CST. FEEDING UNIT-AE1</b>	<b>for all models</b>
Type	2 Front-loading adjustable drawers
Paper Size	A3, A4, A4R, A5R, Custom size 139.7 to 297mm x 182 to 432mm
Paper Capacity and	
Weight	550 sheets (80g/m <sup>2</sup> ) x 2 cassettes, 64 to 90g/m <sup>2</sup>
Dimensions (W x D x H)	565 x 680 x 248mm
Weight	Approx. 24.0kg
<b>INNER FINISHER-B1</b>	<b>for all models</b>
Number of Trays	One stack tray (Optional 2nd Tray; Inner Fin Add. Tray-B1)
Tray Capacity	A4-A5R: 1000 sheets, A3, A4R: 500 sheets
Staple Position	Corner, Double
Staple Capacity	A4: 50 sheets x 30 sets, A4R/A3: 30 sheets x 15 sets
Weight	Approx. 12.5kg
<b>INNER 2-WAY TRAY-G1</b>	<b>for all models</b>
Number of Trays	2 stack tray
Tray Capacity	Tray A: 250 sheets (A4), 100 sheets (A3), Tray B: 100 sheets (A4), 50 sheets (A3)
Weight	Approx. 0.6kg
<b>OTHER ACCESSORIES</b>	Platen Cover Type P, Platen Cover Type Q, Stamp Ink Cartridge-C1, ADF Access Handle-A1, PCL Printer Kit-AF1, PS Printer Kit-AF1, Barcode Printing Kit-B1, Super G3 Fax Board-AG1, FL Cassette-AJ1, FL Cassette-AK1, FL Cassette-AL1, Cassette Spacer-A1, imageRUNNER 2500 Plain Pedestal, 2-Way Unit-B1, Staple-J1, Document Tray-J1, Power Supply Unit-U1, Card Reader Attachment-D3, Canon Card Reader-E1, USB Application 3-Port Interface Kit-A1, CCVI I/F Cable-A1, C-EXV33 TONER BK (imageRUNNER 2520/i, 2525/i, 2530/i), C-EXV32 TONER BK (imageRUNNER 2535/i, 2545/i)
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.	

